··GPU·····

·····MPS · MIG·

····· GPU ····· nvidia-smi ·
·····

·····

·····
·····
····

···· | ·· | ·····

··· | ····· | ·····

··· | ····· | ·····

··· | ····· | ··JobID·····

···/·· | ····· | ·····

··· | ····· | ·····

·····
·····

·····

·····
····· batch·····CUDA·····
·····

·····
····· OOM ·····
····· GPU·····

MPS·MIG ·····

NVIDIA MPS ····· CUDA ·····
·····MIG ····· GPU·····
·····

····· GPU ·····MPS/MIG ·····
····· MIG·····
·····

·····

·····
·····
·····

····· Slurm·Kubernetes ·····
····· GPU ·····
·····

·····

····· GPU·····
·····

```
import csv
from pathlib import Path

fields = ["request_id", "project", "owner", "gpu_type",
          "peak_vram_gb", "start", "end", "interruptible", "status"]
row = ["DEMO-001", "P-DEMO", "user-demo", "…",
       "-", "2026-11-16 09:00", "2026-11-16 10:00", "-", "…"]
path = Path("gpu_requests.tsv")
if path.exists():
    raise FileExistsError(f"…: {path}")
with path.open("x", newline="", encoding="utf-8") as f:
    writer = csv.writer(f, delimiter="\t", lineterminator="\n")
    writer.writerow(fields)
    writer.writerow(row)
print(f"… {path}…")
```

…ID…
…

…

NVIDIA MPS … https://docs.nvidia.com/deploy/mps/latest/when-to-use-mps.html

NVIDIA MPS … https://docs.nvidia.com/deploy/mps/latest/mpsv3-memory-partitioning.html

NVIDIA MIG … https://docs.nvidia.com/datacenter/tesla/mig-user-guide/